ERCO Beamer Floodlight





IK 07
IP 65

DALI





h(m)	E(lx)	D(m)	
		C0	C90
		65.1°	20.2°
1.0	5272	1.28	0.36
2.0	1318	2.55	0.71
3.0	586	3.83	1.07
4.0	330	5.11	1.42
5.0	211	6.39	1.78

A4001305 Graphit m
LED module: 30.4W 3832lm 3000K warm white
DALI-2
Version 3
Construction size L
Spherolit lens, oval flood

Product description
Housing and swivel joint: corrosion-resistant polymer, coated. Optimised surface for reduced accumulation of dirt. Hinge with internal wiring, 90° tilt. Dial: corrosion-resistant aluminium. Mounting plate: polymer, coated. Rotatable through 330°.
2 cable entries. Through-wiring possible. 5-pole terminal block.
DALI control gear.
LED module: high-power LEDs. Collimating lens made of optical polymer.
Luminaire head with non-reflective protective glass, corrosion-resistant cast aluminium, no-rinse surface treatment. Double powder-coated.
Internal lens unit: polymer, black, rotatable through 360°.
Spherolit lens made of optical polymer.
Protection mode IP65: dust-proof and water jet-proof.
Safety class II
Maximum wind load area 0.08m²
Weight 6.44kg
Version with 3000K CRI 97 or 2700K, 3500K CRI 92 available on request.

Technical data

Luminous flux of the luminaire	2552lm
Connected load	35.1W
Luminaire efficacy	73lm/W
Colour deviation	1.5 SDCM
Colour rendition index	CRI 92
Lumen maintenance	L90/B10 >50000h L90 >100000h
LED failure rate	0.1% >50000h
Dimming range	1%-100%
Dimming method	CCR
TLA (Temporal Light Artefacts)	SVM ≤ 0.4; PstLM ≤ 1
LMF	E
Standby power per control gear	0.5W
Luminaires per circuit breaker B16	50

© ERCO GmbH 2026

Technical Region: 220-240V 50/60Hz
We reserve the right to make technical and design changes.
Edition: 28.04.2026
Current version under
www.erco.com/A4001305

Beamer Floodlight

Planning data

Melanopic light effect

Art. no.	Spectrum	MR	MDER
A4001305 (direct)	3000K CRI 92	0.53	0.48

MR Melanopic factor (of luminous radiation) a_mel,v
MDER Melanopic Daylight Efficacy Ratio [gamma]_mel,v,D65

Multiplying the illuminance with the melanopic daylight efficacy ratio MDER gives the melanopic equivalent daylight illuminance MEDI. (MEDI Melanopic Equivalent Daylight Illuminance [lx] E_v,mel,D65 [lx]).

Cleaning (a)	1				2				3			
Ambient conditions	P	C	N	D	P	C	N	D	P	C	N	D
LMF	0.96	0.94	0.90	0.86	0.93	0.91	0.86	0.81	0.92	0.90	0.84	0.79

Hours of operation (h)	1000	5000	10000	20000	30000	40000	50000
LLMF	1.00	0.99	0.98	0.96	0.94	0.92	0.90
LSF	1	1	1	1	1	1	1

MF LMFxRSMFxLLMFxLSF
MF Maintenance Factor
LMF Luminaire Maintenance Factor
RSMF Room Surface Maintenance Factor
LLMF Lamp Lumens Maintenance Factor
LSF Lamp Survival Factor
P Room pure
C Room clean
N Room normal
D Room dirty

Data according to regulations
2019/2020/EU supplemented by 2021/341/EU and 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance

This product contains a light source of efficiency class E
Due to thermal and photometric properties as well as to protect electronic components from ESD (electrostatic discharge) the light source cannot be changed by the customer.

ID EPREL: 1784555
Model identifier: 3000068452
Download data sheets for control gear and disassembly instructions at www.erco.com/slr

Technical data in accordance with international norms and standards

IEC 60598	Luminaires – Part 1+2: general requirements, specific requirements and tests
IEC 62031	LED modules for general lighting – safety requirements
IEC 62471	Photobiological safety of lamps and lamp systems
EN13032-4	Light and lighting – measurement and representation of photometric data
CIE 13	Method of measuring and specifying colour rendering properties of light sources

All technical data is subject to industry-standard tolerances.
Also see www.erco.com/erco-led

For explanations of the symbols and abbreviations used and other general information, see www.erco.com/symbols

Beamer Floodlight

Planning data



∅ 60–89mm



∅ 60–89mm



∅ 60–89mm



Beamer Floodlight

Accessories

AC002177
Lens unit spot
Polymer, black, rotatable through 360°.
Replacement without tools.
Darklight lens made of optical polymer.
Optical cut-off 40°.
Weight 0.36kg
CE

AC002179
Lens unit zoom spot
Polymer, black, rotatable through 360°.
Replacement without tools.
Anti-reflective zoom lens made of optical polymer, infinitely variable focus.
Weight 0.24kg
CE



AC002175
Lens unit flood
Polymer, black, rotatable through 360°.
Replacement without tools.
Darklight lens made of optical polymer.
Optical cut-off 30°.
Weight 0.42kg
CE



AC006035
Softening lens
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.10kg



AC002173
Lens unit wide flood
Polymer, black, rotatable through 360°.
Replacement without tools.
Darklight lens made of optical polymer.
Optical cut-off 30°.
Weight 0.48kg
CE



AC006043
Sculpture lens
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.10kg



AC002170
Lens unit extra wide flood
Polymer, black, rotatable through 360°.
Replacement without tools.
Darklight lens made of optical polymer.
Weight 0.50kg
CE



AC006038
Cold Filter
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg



AC002171
Lens unit oval flood
Polymer, black, rotatable through 360°.
Replacement without tools.
Anti-reflective Spherolit lens made of optical polymer.
Weight 0.30kg
CE
AC006062



AC006036
Cold Filter Plus
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg



AC002172
Lens unit wallwash
Polymer, black, rotatable through 360°.
Replacement without tools.
Anti-reflective Spherolit lens made of optical polymer.
Weight 0.30kg
CE
AC006062



AC006049
Warm Filter
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg

ERCO

Beamer Floodlight

Accessories



AC006048
Warm Filter Plus
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg

AC006039
Skintone Filter
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg



AC006037
Blue Light Filter
Filter holder: polymer, black, rotatable through 360°. Replacement without tools.
Weight 0.11kg

AC006062
Lens Unit Adapter
Polymer, black, rotatable through 360°.
Replacement without tools.
Weight 0.06kg
AC002179

34974.000
Distribution box, IP68
with four cable entries, 7-25mm.
Polymer.
ø 102mm, L 305mm.
Weight 0.45kg
CE IP 68 3m UKCA

56010.000
Casambi DALI Gateway
Enables the control of DALI luminaires via Casambi Bluetooth.
Input voltage: 220-240V; 50/60Hz.
Max. number of controllable luminaires: 25 (depending on the number of control gear units per luminaire. The data sheet of the luminaire specifies this information.)
When assembled in the housing supplied, the gateway is protected against ingress of dust and strong jets of water (IP65).
Setup of the gateway via Casambi app (Android/iOS) with Bluetooth Low Energy (BLE)-capable mobile devices.
Operation only in Casambi Evolution networks.
Outgoing DALI control lines must be designed for mains voltage.
The gateway provides 4 DALI group addresses, enabling 4 monochrome luminaire groups to be dimmed. The luminaires are assigned to a DALI group address in the Casambi app.
With tunable white luminaires, up to 3 luminaire groups can be dimmed differently. The luminaires are assigned to a DALI group address in the Casambi app. The colour temperature is set simultaneously for all connected luminaires via a broadcast command. No special settings or assignments are necessary to adjust the colour temperature.
RGBW luminaires are automatically recognised by the gateway and controlled simultaneously via broadcast command; no special settings or assignments are necessary.
Weight 0.47kg
CE IP 65 UKCA





34953.000
Attachment
for upright supporting pole ø 60-89mm.
Housing: stainless steel. Graphit m, powder-coated.
Clamping plate or second attachment for fixing to be ordered separately.
Upright supporting pole ø 60-89mm to be ordered separately.
Weight 0.75kg



ERCO

Beamer Floodlight

Accessories



34954.000
Clamping plate
for fixing cantilever arm or attachment on upright supporting pole ø 60–89mm.
Housing: stainless steel. Graphit m, powder-coated.
Cantilever arm or attachment to be ordered separately.
Weight 0.61kg
34953.000
34955.000





33974.000
Ground socket
Metal, hot-dip galvanised.
Weight 2.55kg
CE UK CA





34955.000
Cantilever arm
for standing luminaire installation on upright supporting pole ø 60–89mm or wall.
Housing: stainless steel. Graphit m, powder-coated.
Clamping plate or second cantilever arm for fixing on upright supporting pole to be ordered separately.
Upright supporting pole ø 60-89mm to be ordered separately.
Weight 2.00kg
CE UK CA



33981.000
Concrete anchor
Mounting plate with threaded bar and fixing nuts M10. Individual parts to be assembled on-site.
Individual parts to be assembled on-site.
Weight 0.54kg
CE UK CA





33982.000
Mounting plate
Corrosion-resistant cast aluminium, No-Rinse surface treatment. Graphit m, double powder-coated.
Weight 1.67kg
CE UK CA





34991.000
Spacer
for surface-mounted cables.
Corrosion-resistant cast aluminium, No-Rinse surface treatment. Graphit m, double powder-coated.
Weight 0.40kg
CE UK CA